



Asphalt repair



Product name	Article no.	Unit
Potmix Asphalt Repair 7 kg	11010	bucket
Potmix Asphalt Repair 20 kg	11020	bucket
Potmix Asphalt Repair 22 kg	11030	bag
Potmix Asphalt Repair 500 kg	11090	bigbag

Delivered on EUR pallets.

Description:

Potmix Asphalt Repair is an asphalt mix for repairing asphalt surfacing and for asphaltting small areas. The asphalt mix has a soft consistency, and hardens when compressed and with time in contact with air. The product does not require any additives, special tools or previous experience of laying asphalt. Potmix Asphalt Repair does not stay sticky or lose its colour after hardening, and works equally well in summer and winter. The size of the stones is 2-8 mm. This gives very good durability and an appearance very like the old surrounding asphalt.

How to use:

1. Prepare the area to be repaired by brushing away all rubbish. Fill up with gravel or sand leaving a depth of about four cm for the asphalt. A four cm layer of asphalt will support heavy traffic. For lighter traffic, a thinner layer can be laid.
2. Then spread out the asphalt on the area. Compress it with a suitable tool such as an asphalt roller or hand rammer. It is a good idea to spread the asphalt a few cm thicker in the centre of the area, and then to compress from the centre outwards.
3. Traffic can be allowed back immediately. The greater the compression when spread out, and by allowing traffic back, the quicker the asphalt will harden.

Producer: Potmix Products AB, Tel. +46 16 422 967, Fax +46 16 132 967
www.potmix.com, info@potmix.com

